

Keпо Pelectro 20 - Technical Characteristics



Weight	kg	AC 258
Height	mm	1280
Width	mm	665
Depth	mm	830
Flue pipe diameter	mm	80
Draft	mbar	0,10
Pellet tank capacity	kg	62
Electricity consumption at start - pellets/electricity	W	390/18000
Electricity consumption during operation - pellets/electricity	W	110/18000
Standby power consumption	W	4
Nominal voltage	Vac	3x400
Nominal frequency	Hz	50
Water pipe diameter	"	1
Safety valve pipe diameter	"	1/2
Pump flow rate	l/h	1300
Expansion dish	l	8
Exhaust gas temperature in nominal mode	°C	119
Exhaust gas temperature in minimum operating mode	°C	63
Amount of water in the boiler	l	53
Boiler power (pellet)	kW	min 5,79 - max 18,50
Boiler power (electricity)	kW	min 9 - max 18
Pellet consumption	kg/h	min 1,37 - max 4,56
Energy utilization	%	min 88,45 - nominal 91,52
Water temperature setting range	°C	min 60 - max 80
Minimum return water temperature	°C	50
Boiler water pressure	bar	min 0,60 - max 2,50
Recommended pellet class	EN303-5 EN plus	C1 - A1
Boiler class	-	5
Boiler energy efficiency	-	A+
Heating surface	m ²	100-160

NOTE—The table shows the recommended boiler power according to the heating surface. Factors influencing the determination of boiler power are the average outdoor temperature during winter, building insulation, temperature that is set inside the building, calculation related to the central heating system inside the building. All buildings and all user needs are unique and based on that, your designated expert is obliged to calculate energy losses, assess existing installations and determine the boiler power adequate for your quarters based on that.



CE Mark Information
Certification body: TÜV Rheinland Poland
Reference: 57581/ET/2015